

November 2025

PRODUCT DATA SHEET

Product	Rustins Quick Dry Tougher than Plastic Coating
Type	Two-part water-borne clear coating.
Intended Use	For use on interior woodwork such as kitchen worktops.
Special Features	Quick drying. Water based. Non-flammable.
Preparation	Ensure the surface is dry and free of grease, soap and contaminants.
Application	Stir part 'A' thoroughly. Add part 'B' and stir thoroughly for a few minutes to ensure full mixing. Using the widest roller/brush practical for the job apply the mixed product to the clean surface in an even manner and avoid over-brushing. The mixing ratio of part A to part B is 20:1 by volume. Mixed working time: 24 hours at 20 Centigrade once catalysed.
Coats	As required.
Drying Time	Touch dry in 30 minutes.
Re-coating Time	Approximately 2 hours.
Application Temp.	Ideally 15-20°C. Do not apply below 10°C.
Coverage	12 square metres per 1 Litre.
Maintenance	Clean the surface with a mild soapy solution.
Compatibility	Suitable for use on wood surfaces. If in doubt carry out a test coating.
Settlement	STIR WELL BEFORE USE.
Shelf-life/Storage	Without combining part A and part B, 12 months if stored in a cool dry place
Hazards	Contains cobalt 6,2-octyl-2h-isothiazol-3-one. May produce an allergic reaction. Keep away from children. Avoid contact with skin and eyes. Wear protective gloves and eye protection. For full SDS visit www.rustins.co.uk
Clean-Up	Clean equipment while wet with soapy water.
Sizes	250ml, 1L.