



Technical data sheet

Holz 2000

Protect wood

Cod. 0080



DESCRIPTION

HOLZ 2000 is a professional product for the treatment and protection of wood.

The gradual and not excessively rapid drying allows for deep penetration, without post-application stains and halos. Of good aggressiveness, without altering the wood fiber, it guarantees an excellent result that prevents and definitively eliminates harmful agents of the wood such as woodworms and parasites in general.

Contains pyrethroid additives.

YIELD

6/8 m² depending on the absorption of the support.

FIELDS OF APPLICATION

Furniture, doors, fixtures in general.

Beams, ceilings, structural elements and coverings in general.

CLEANING AND DILUTION

Product ready for use.

Characteristics	U.M.	Value
Appearance		liquid
Color		colorless
Odour		characteristic
Solubility		white spirit
Density	g/cm ³	0,81 ± 0,02



HOW TO USE



On a corroded and weakened support, apply Holz 2000 liberally by brush, spray or, if possible, by immersion.

To improve the effectiveness of the treatment, it is advisable to cover the support with a sheet or plastic, which prevents transpiration.



Wait 12-24 hours depending on the type of wood and the quantity of product applied.



If the treatment is preventive, post-drying, proceed with grouting, sanding and subsequent finishing.



If the treatment is curative, evaluate the need for at least one new application of Holz 2000 before proceeding to any subsequent work phase.

TECHNICAL RECOMMENDATIONS

Always carry out a preliminary test on a sacrifice zone to check if the effect corresponds to the desired one.

Avoid contact with other materials that may be incompatible with the product (water, oxidizing agents).

RECOMMENDED CYCLES

To complete the processing cycle, the following products are recommended:

- Holzmasse 1800XX – quick drying putty
- Holz Haerter cod 0641– wood consolidant

PACKAGING

Cod. 0080	12x100ml with syringe
Cod. 0081	12x100ml without syringe
Cod. 0082	12x250ml with syringe
Cod. 0083	2x250ml without syringe
Cod. 0084	12x1Lt
Cod. 0085	2x5Lt
Cod. 0086	1x20Lt
Cod. 0087	1x10Lt

STORAGE

Keep the material in clean, well-ventilated environments, away from heat sources and direct sunlight, possibly between the minimum temperature of 5° C and the maximum temperature of 35° C. The product should preferably be stored in the original containers. The product has a shelf life of 24 months from the date of production.

WARNINGS

Read the safety data sheet before use.

Respect the safety regulations in force.

Product for professional use.

Our technical data sheets are drawn up based on average results of our tests. However, our technical advice is given in good faith but without guarantee.

In fact, different supports, application conditions, systems, dilutions are an integral part of the final result and often beyond any control. The user must try the products supplied to verify whether they are suitable for his needs. For our part, we guarantee the continuity of the chemical-physical characteristics.

Product code: **0080**

Revision: **02 del 10.09.2024**