

DANISH OIL (MEKO-FREE)

Page: 1

Compilation date: 04/06/2021

Revision date: 22/10/2021

Revision No: 4

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: DANISH OIL (MEKO-FREE)

Product code: DANO

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Rustins Ltd.

Waterloo Road Cricklewood London NW2 7TX

Tel: +44 (0)208 450 4666 Fax: +44 (0)208 452 2008

United Kingdom

Email: rustins@rustins.co.uk

1.4. Emergency telephone number

Emergency tel: +44 0208 450 4666

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 3: H226; Muta. 1B: H340; Carc. 1B: H350; -: EUH208

Most important adverse effects: Contains cobalt 6, 2-octyl-2h-isothiazol-3-one. May produce an allergic reaction.

Flammable liquid and vapour. May cause genetic defects. May cause cancer.

2.2. Label elements

Label elements:

UFI: MP2N-QRQC-5F0Y-EMA0

Hazard statements: EUH208: Contains cobalt 6, 2-octyl-2h-isothiazol-3-one. May produce an allergic

reaction.

H226: Flammable liquid and vapour. H340: May cause genetic defects.

H350: May cause cancer.

Hazard pictograms: GHS02: Flame

GHS08: Health hazard





DANISH OIL (MEKO-FREE)

Page: 2

Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P241: Use explosion-proof electrical/ventilating/lighting/... equipment.

P280: Wear protective gloves and eye protection.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water .

P308+P313: IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

Other hazards: Danger of serious damage to health by prolonged exposure.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY; LOW BOILING POINT YDROGEN TREATED NAPHTHA; [A COMPLEX COMBINATION OF HYDROCARBONS OBTAINED BY TREATING A PETROLEUM FRACTION WITH HYDROGEN IN THE PRESENCE OF A CATALYST. IT CONSISTS OF HYDROCARBONS HAVING CARBO

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-150-3	64742-48-9	-	Carc. 1B: H350; Muta. 1B: H340; Asp. Tox. 1: H304	50-70%
COBALT 6				
-	13586-82-8	-	Eye Irrit. 2: H319; Skin Sens. 1: H317; Repr. 2: H361f; Aquatic Chronic 3: H412	<1%
2-ETHYLHEX	ANOIC ACID			
205-743-6	149-57-5	-	Repr. 2: H361d	<1%
METHANOL				
200-659-6	67-56-1	-	Flam. Liq. 2: H225; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT SE 1: H370	<1%

DANISH OIL (MEKO-FREE)

Page: 3

2-OCTYL-2H-ISOTHIAZOL-3-ONE

247-761-7	26530-20-1	-	Acute Tox. 3: H331; Acute Tox. 3: H311;	<1%
			Acute Tox. 4: H302; Skin Corr. 1B:	
			H314; Skin Sens. 1: H317; Aquatic	
			Chronic 1: H410; Aquatic Acute 1:	
			H400	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still

on skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: No symptoms.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers. Water spray. Alcohol resistant foam. Carbon dioxide. Dry chemical

powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes. Flammable. Forms explosive air-vapour mixture.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

DANISH OIL (MEKO-FREE)

Page: 4

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Evacuate the area immediately.

Notify the police and fire brigade immediately. Eliminate all sources of ignition. Turn

leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding. Alert the

neighbourhood to the presence of fumes or gas.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Clean-up should be dealt with only by qualified personnel

familiar with the specific substance. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure

which may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in

the air. Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from

sources of ignition. Prevent the build up of electrostatic charge in the immediate area.

Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

METHANOL

Workplace exposure limits:

Respirable dust:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	266 mg/m3	333 mg/m3	-	-

DANISH OIL (MEKO-FREE)

Page: 5

2-OCTYL-2H-ISOTHIAZOL-3-ONE

UK	0.05 mg/m3	0.05 mg/m3	-	-
----	------------	------------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Environmental: Refer to specific Member State legislation for requirements under Community

environmental legislation.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Yellow-brown

Odour: Paraffinic.

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: Insoluble

Flash point°C: 38

Also soluble in: Most organic solvents.

Viscosity: Oily

Boiling point/range°C: No data available. Melting point/range°C: No data available.

Flammability limits %: lower: No data available. upper: No data available.

Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available. Vapour pressure: No data available.

Relative density: 0.84 @ 20C pH: Approx. 7

VOC g/I: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

DANISH OIL (MEKO-FREE)

Page: 6

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

2-ETHYLHEXANOIC ACID

ORL	RAT	LD50	3	gm/kg
SKN	RBT	LD50	1260	μl/kg

METHANOL

IVN	RAT	LD50	2131	mg/kg
ORL	MUS	LD50	7300	mg/kg
ORL	RAT	LD50	5628	mg/kg

2-OCTYL-2H-ISOTHIAZOL-3-ONE

ORL	RAT	LD50	550	mg/kg
SKN	RBT	LD50	690	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Germ cell mutagenicity		Hazardous: calculated
Carcinogenicity		Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: No symptoms.

DANISH OIL (MEKO-FREE)

Page: 7

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT

including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid

lacquer basePaint related product

(PAINT

including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid

lacquer base)

14.3. Transport hazard class(es)

Transport class: III

DANISH OIL (MEKO-FREE)

Page: 8

14.4. Packing group

Packing group: 3

14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E **Transport category:** 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation

(EU) 2015/830

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH208: Contains cobalt 6, 2-octyl-2h-isothiazol-3-one. May produce an allergic

reaction.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H301: Toxic if swallowed.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H311: Toxic in contact with skin.

H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H340: May cause genetic defects.

H350: May cause cancer.

H361d: Suspected of damaging the unborn child.

H361f: Suspected of damaging fertility.

H370: Causes damage to organs.

H410: Very toxic to aquatic life with long lasting effects.

DANISH OIL (MEKO-FREE)

Page: 9

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.