

SCRATCH COVER - LIGHT MEDIUM & DARK

Page: 1

Compilation date: 11/09/2012

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: SCRATCH COVER - LIGHT MEDIUM & DARK

Product code: SC

Synonyms: SCRATCH COVER

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Rustins Ltd

Waterloo Road Cricklewood London NW2 7TX

United Kingdom **Tel:** +44 (0)208 450 4666

Fax: +44 (0)208 452 2008

Email: rustins@rustins.co.uk

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: -: R10; Xi: R36/38; Xn: R65; -: R66; -: R67

Most important adverse effects: Flammable. Irritating to eyes and skin. Harmful: may cause lung damage if swallowed.

Repeated exposure may cause skin dryness or cracking. Vapours may cause

drowsiness and dizziness.

2.2. Label elements

Label elements under CHIP:

Hazard symbols: Harmful.



Risk phrases: R10: Flammable.

R36/38: Irritating to eyes and skin.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

SCRATCH COVER - LIGHT MEDIUM & DARK

Page: 2

Safety phrases: S23: Do not breathe fumes.

2.3. Other hazards

PBT: This substance is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

NAPTHA (PETROLEUM) HYDROTREATED HEAVY

EINECS	CAS	CHIP Classification	CLP Classification	Percent
265-150-3	64742-48-9	Xn: R65; -: R66; -: R67	-	30-50%
PLEXIGUM P2	4 SOLUTION			
-	-	Xn: R20; Xi: R36/37/38; Xn: R65	-	1-10%
3-BUTOXYPRO	PAN-2-OL			
225-878-4	5131-66-8	Xi: R36/38	Eye Irrit. 2: H319; Skin Irrit. 2: H315	10-30%
SOLVENT NAF	PHTHA			
-	-	-: R10; Xn: R20; Xi: R36/37/38; N: R51/53: Xn: R65	-	1-10%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove contaminated clothing. Wash skin thoroughly with soap and water or use a

proprietry skin cleaner. Do NOT use solvents or thinners. If irritation persists seek

medical attention.

Eye contact: Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least

10 minutes, holding the eyelids apart. Seek medical attention.

Ingestion: If accidentally swallowed, wash mouth out with water. Do not induce vomiting, keep at

rest and obtain medical attention.

Inhalation: Remove to fresh air, keep the patient warm and at rest. If breathing has stopped,

administer artificial respiration. Give nothing by mouth if unconscious, place in the

recovery position and seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Irritation. Repeated or prolonged contact may cause defatting of the skin leading to

irritation and dermatitis.

Eye contact: Irritation with short term redness and stinging.

Ingestion: Large doses may cause nausea and diarrhoea. Aspiration into the lungs after ingestion

will cause severe lung damage and may cause fatal pneumonitis.

Inhalation: May cause irritation of the respiratory tract. May cause drowsiness, dizziness, headache.

SCRATCH COVER - LIGHT MEDIUM & DARK

Page: 3

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide (CO2). Dry chemical powder. Alcohol resistant foam. Sand or earth. DO

NOT USE WATER.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In a fire, hazardous decompostition products such as smoke and Carbon Monoxide may

be produced.

5.3. Advice for fire-fighters

Advice for fire-fighters: Exposure to decomposition products may be a hazard to health. Appropriate self-

contained breathing apparatus may be required. Cool closed containers exposed to fire with water spray. Do NOT allow run-off from fire fighting to enter drains or water courses.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Ventilate the area. Eliminate all sources of ignition. No Smoking. Avoid inhaling vapour.

Avoid contact with skin and eyes. Mark out the contaminated area with signs and prevent

access to unauthorised personnel.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. If the product enters drains or sewers, the local

water company should be contacted immediately. In the case of contamination of

streams, rivers or lakes contact the relevant environment agency.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Contain and collect spillages with non-combustible absorbent materials, e.g. sand,

earth, vermiculite. Transfer into a suitable container for disposal in accordance with the waste regulations (see section 13) Do not use equipment in clean-up procedure which

may produce sparks. Clean preferably with a detergent, avoid the use of solvents.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid inhalation of vapour. Avoid skin

and eye contact. Smoking, eating and drinking should be prohibited in areas of storage and use. Exclude sources of heat, sparks and open flame. Earth any equipment used in handling. Use non-sparking tools. The Manual Handling Operations Regulations may

apply to the handling of containers of this product.

SCRATCH COVER - LIGHT MEDIUM & DARK

Page: 4

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Keep in cool, dry, ventilated storage and tightly closed containers. Keep away from direct

sunlight. Exclude sources of heat, sparks and open flame. Take precautionary measures to prevent product spills into drains, the ground or waters. Although the storage of this product is not subject to specific statutory requirements, the principles contained in the HSE guidance note Storage of Flammable Liquids in containers,

should be observed.

Suitable packaging: Ideally, keep in original container. If transfer is necessary use glass or coated steel

containers.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: Not applicable.

8.2. Exposure controls

Engineering measures: Provide adequate ventilation. Where reasonably practicable, this should be achieved by

the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and/or solvent vapours below the relevant occupational exposure limits, suitable respiratory protective equipment should be worn

(see Respiratory protection below).

Respiratory protection: If there is a risk of exposure to high vapour concentrations, use respiratory protective

equipment. All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to

meet the requirements of the COSHH Regulations.

Hand protection: Wear Nitrile gloves.

Eye protection: Eye protection designed to protect against liquid splashes should be worn. Ensure eye

bath is to hand.

Skin protection: Overalls are normally suitable, PVC apron if risk of splashing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colour Range

Odour: Paraffinic.

Solubility in water: Not miscible

Viscosity: Non-viscous

Boiling point/range °C: 150-190 Flash point °C: 38

Relative density: 0.850 @ 20 C

SCRATCH COVER - LIGHT MEDIUM & DARK

Page: 5

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Chemical stability: Stable under normal storage and handling conditions (see Section 7).

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid: Avoid heat, flames and sparks. Sources of ignition. Direct sunlight.

10.5. Incompatible materials

Materials to avoid: Oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In a fire, hazardous decomposition products such as smoke and carbon monoxide may

be produced.

Section 11: Toxicological information

11.1. Information on toxicological effects

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Irritation. Repeated or prolonged contact may cause defatting of the skin leading to

irritation and dermatitis.

Eye contact: Irritation with short term redness and stinging.

Ingestion: Large doses may cause nausea and diarrhoea. Aspiration into the lungs after ingestion

will cause severe lung damage and may cause fatal pneumonitis.

Inhalation: May cause irritation of the respiratory tract. May cause drowsiness, dizziness, headache.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: Not applicable.

12.2. Persistence and degradability

Persistence and degradability: There is no data available on the product itself. Expected to biodegrade slowly.

SCRATCH COVER - LIGHT MEDIUM & DARK

Page: 6

12.3. Bioaccumulative potential

Bioaccumulative potential: There is no data available on the product itself. Not expected to bioaccumulate.

12.4. Mobility in soil

Mobility: Immiscible in water. Partially volatile. Partially absorbed into soil. The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.

12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

SCRATCH COVER - LIGHT MEDIUM & DARK

Page: 7

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: H315: Causes skin irritation.

H319: Causes serious eye irritation.

R10: Flammable.

R20: Harmful by inhalation.

R36/37/38: Irritating to eyes, respiratory system and skin.

R36/38: Irritating to eyes and skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product. As the specific

conditions of use of the product are outside the supplier's control, the user is

responsible for ensuring that the requirements of relevant legislation are complied with.