



SAFETY DATA SHEET
PLASTIC COATING THINNERS BOTTLES

Page 1
Issued: 31/07/04
Revision No: 2

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: PLASTIC COATING THINNERS BOTTLES
EINECS number: -
Product code: PCTHB
Synonyms: PLASTIC COATING THINNERS - BOTTLES
Company name: Rustins Ltd
Waterloo Road
Cricklewood
London
NW2 7TX
United Kingdom
Tel: +44 (0)208 450 4666
Fax: +44 (0)208 452 2008
Emergency tel: +44 (0)208 205 8709

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: ETHANOL 30-50%
CAS: 64-17-5
EINECS: 200-578-6
[F] R11

- METHANOL 1-10%
CAS: 67-56-1
EINECS: 200-659-6
[F] R11; [T] R23/24/25; [T] R39/23/24/25
- BUTAN-1-OL 50-70%
CAS: 71-36-3
EINECS: 200-751-6
[-] R10; [Xn] R22; [Xi] R37/38; [Xi] R41; [-] R67

3. HAZARDS IDENTIFICATION

Main hazards: Highly flammable. Harmful by inhalation, in contact with skin and if swallowed. Irritating to respiratory system and skin. Risk of serious damage to eyes.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: Irritation. Repeated or prolonged contact may cause defatting of the skin leading to irritation and dermatitis.

Eye contact: Irritation, reddening and transient corneal damage.

Ingestion: May cause dizziness, loss of coordination, loss of consciousness, temporary or permanent blindness, coma and death.

[cont...]

SAFETY DATA SHEET

PLASTIC COATING THINNERS BOTTLES

Inhalation: There may be irritation of nose, throat and respiratory tract. Dizziness, loss of coordination, nausea and vomiting may occur.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove contaminated clothing, drench skin with plenty of water. If there is any skin damage or if irritation persists seek medical attention. Wash contaminated clothing before reuse.

Eye contact: Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart, and seek medical attention.

Ingestion: Do not induce vomiting. Wash out mouth with water. Get medical attention immediately.

Inhalation: Remove to fresh air, keep the patient warm and at rest. If there is difficulty in breathing, properly trained personnel may administer oxygen. If breathing has stopped, administer artificial respiration (NOT mouth to mouth). Give nothing by mouth if unconscious, place in the recovery position and seek medical attention.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Water spray, fog or mist. Do NOT use water jet. Carbon dioxide (CO₂). Dry chemical powder. Alcohol resistant foam. Sand or earth.

Exposure hazards: Highly flammable. May explode in a fire. Solvent vapours may form explosive mixtures with air. The vapour is heavier than air and may travel along the ground, collect in work pits and cellars, creating a fire and respiratory hazard. Vapour explosion and poison hazard indoors, outdoors and in sewers. In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Protection of fire-fighters: Wear protective clothing to prevent contact with skin and eyes. Wear self-contained breathing apparatus. Cool closed containers exposed to fire with water spray. Do NOT allow run-off from fire fighting to enter drains or water courses.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Ventilate the area. Eliminate all sources of ignition. No Smoking. Avoid inhaling vapour. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing (see section 8).

Environmental precautions: Do not discharge into drains or rivers. If the product enters drains or sewers, the local water company should be contacted immediately. In the case of contamination of streams, rivers or lakes contact the relevant environment agency. Vapour explosion and poison hazard indoors, outdoors and in sewers.

Clean-up procedures: Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth, vermiculite. Transfer into a suitable container for disposal in accordance with the waste regulations (see section 13) Do not use equipment in clean-up procedure which may produce sparks. Clean preferably with a detergent, avoid the use of solvents. Clean-up personnel should use respiratory and/or liquid contact protection.

SAFETY DATA SHEET
PLASTIC COATING THINNERS BOTTLES

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid inhalation of vapour. Avoid skin and eye contact. Smoking, eating and drinking should be prohibited in areas of storage and use.

Emergency shower and eye wash facilities should be readily available. Exclude sources of heat, sparks and open flame. Earth any equipment used in handling. Use non-sparking tools.

Storage conditions: Store in a cool, dry place. Keep container tightly closed. Keep away from direct sunlight.

Exclude sources of heat, sparks and open flame. Take precautionary measures to prevent product spills into drains, the ground or waters. Further guidance is contained in the HSE guidance note Storage of Flammable Liquids in Containers.

Suitable packaging: Ideally, keep in original container. If transfer is necessary use glass, coated steel or plastic containers. Do NOT store in lead, zinc, tin or aluminium.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: ETHANOL

TWA (8 hr exposure limit): 1920 mg/m³ (OES)

- METHANOL

TWA (8 hr exposure limit): 266 mg/m³ STEL (15 min exposure limit): 333 mg/m³ (OES)

- BUTAN-1-OL

STEL (15 min exposure limit): 154 mg/m³ (OES)

Engineering measures: Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and/or solvent vapours below the relevant occupational exposure limits, suitable respiratory protective equipment should be worn (see Respiratory protection below).

Respiratory protection: If there is a risk of exposure to high vapour concentrations, use respiratory protective equipment. All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH Regulations.

Hand protection: Wear Nitrile gloves.

Eye protection: Eye protection designed to protect against liquid splashes should be worn. Ensure eye bath is to hand.

Skin protection: Overalls are normally suitable, PVC apron if risk of splashing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Clear.

Odour: Alcoholic

Solubility in water: Partially miscible.

SAFETY DATA SHEET

PLASTIC COATING THINNERS BOTTLES

Boiling point/range°C: 77.5

Flash point°C: 20

Relative density: 0.804 @ 20 C

10. STABILITY AND REACTIVITY

Stability: Stable under normal storage and handling conditions (see Section 7).

Conditions to avoid: Avoid heat, flames and sparks. Direct sunlight.

Materials to avoid: Strong acids. Strong oxidising agents.

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: ETHANOL

IVN RAT LD50 1440 mg/kg
ORL MUS LD50 3450 mg/kg
ORL RAT LD50 7060 mg/kg

- METHANOL

IVN RAT LD50 2131 mg/kg
ORL MUS LD50 7300 mg/kg
ORL RAT LD50 5628 mg/kg

- BUTAN-1-OL

IVN RAT LD50 310 mg/kg
ORL MUS LD50 2680 mg/kg
ORL RAT LD50 790 mg/kg

Routes of exposure: This product has not been tested for toxicity. The toxicological properties given in this section are based on those of the solvents. May cause skin/eye irritation and corrosive burns. Defatting, drying and cracking of skin. Swallowing may cause blindness, severe internal injury, unconsciousness and death. High vapour concentrations may cause severe lung damage. Vapour irritates the eyes and the respiratory tract.

12. ECOLOGICAL INFORMATION

Mobility: Partially miscible. Volatile. Partially absorbed into soil.

Persistence and degradability: Expected to be biodegradable.

Bioaccumulative potential: Not expected to bioaccumulate.

Other adverse effects: There is no data available on the product itself.

13. DISPOSAL CONSIDERATIONS

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

SAFETY DATA SHEET
PLASTIC COATING THINNERS BOTTLES

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 1263 **ADR Class:** 3
Labelling: 3 **Hazard ID no:** 33

**IMDG / IMO**

UN no: 1263 **Class:** 3
Packing group: II **EmS:** 3-05
Marine pollutant: . **Labelling:** 3

IATA / ICAO

UN no: 1263 **Class:** 3
Packing group: II **Packing instructions:** 307
Labelling: 3

15. REGULATORY INFORMATION

Hazard symbols: Highly flammable.
Harmful.



Risk phrases: R11: Highly flammable.
R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.
R37/38: Irritating to respiratory system and skin.
R41: Risk of serious damage to eyes.

Safety phrases: S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S23: Do not breathe ...
S16: Keep away from sources of ignition - No smoking.
S7: Keep container tightly closed.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions. Safety Data Sheet complies with UK regulatory references in accordance with CHIP 3.

SAFETY DATA SHEET
PLASTIC COATING THINNERS BOTTLES

16. OTHER INFORMATION

Risk phrases used in s.2: R11: Highly flammable.
R23/24/25: Toxic by inhalation, in contact with skin and if swallowed.
R39/23/24/25: Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
R10: Flammable.
R22: Harmful if swallowed.
R37/38: Irritating to respiratory system and skin.
R41: Risk of serious damage to eyes.
R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.